

# EdgePro Low Profile® Paver Restraint



## Product Configurations

Item 1306	EdgePro Low Profile® – 7.5' Bundled
Item 1326	EdgePro Low Profile® – 15' Bundled

## Product Specifications

Material:	Engineered Rigid PVC Alloy
Weight:	0.40 lbs. per linear foot (nominal)
Vertical Wall Height:	1.20 in. (nominal)
Horizontal Base Width:	3.00 in. (nominal)
Vertical Wall Thickness:	0.23 in. (nominal)
Horizontal Base Thickness:	0.25 in. (nominal)



## Packaging Specifications


12 – 7.5' lengths/bundle, 49 bundles/pallet (4,410 ft.)  
6 – 15' lengths/bundle, 50 bundles/pallet (4,500 ft.)

## Physical Property Testing

Impact Strength	ASTM Test D-256	Min. 120 lbs./in.
Tensile Strength	ASTM Test D-638	Min. 5,000 PSI
Flexural Modules	ASTM Test D-790	Min. 280,000 PSI

EdgePro® Paver Restraint products pass Ultraviolet and Weathering Tests per Federal Std. 191 A Method 5804.

## Paver Restraint Accessories

Steel Stakes 60-Count	8" Spiral Steel Spikes 50# Case	10" Spiral Steel Spikes 50# Case	10" Round Steel Spikes 50# Case	12" Round Steel Spikes 50# Case	10" Spiral Nylon Spikes 150-Count	10" Round Nylon Spikes 150-Count
						
Item 1900	SPIKE8BS	SPIKE10BS	SPIKE10BR	SPIKE12BR	SPIKE10NS	SPIKE10NR



## Dimex Limited Lifetime Warranty

EdgePro® Paver Restraint products are guaranteed to be free from manufacturing defects and will not crack, rot, or deteriorate when handled and installed according to recommended guidelines.



28305 State Route 7  
Marietta, OH 45750  
www.edgepro.com

Phone: 740-374-3100  
Toll Free: 800-334-3776  
Fax: 740-374-5420