

NovaFlex™ Paver Restraint



Product Configurations

- Item 1216 NovaFlex™ Paver Restraint – 7.5' Boxed
- Item 1318 NovaFlex™ Paver Restraint – 15' Boxed

Product Specifications

Material:	Engineered Rigid PVC Alloy
Weight:	0.32 lbs. per linear foot (nominal)
Vertical Wall Height:	1.75 in. (nominal)
Horizontal Base Width:	2.70 in. (nominal)
Vertical Wall Thickness:	0.16 in. (nominal)
Horizontal Base Thickness:	0.16 in. (nominal)



Packaging Specifications








12 – 7.5' lengths/box, 48 boxes/pallet (4,320 ft.), 6 – 15' lengths/box, 50 boxes/pallet (4,500 ft.)

Physical Property Testing

Impact Strength	ASTM Test D-256	Min. 120 lbs./in.
Tensile Strength	ASTM Test D-638	Min. 5,000 PSI
Flexural Modules	ASTM Test D-790	Min. 280,000 PSI

NovaEdge Paver Restraint products pass Ultraviolet and Weathering Tests per Federal Std. 191 A Method 5804.

Paver Restraint Accessories

Steel Stakes 60-Count	8" Spiral Steel Spikes 50# Case	10" Spiral Steel Spikes 50# Case	10" Round Steel Spikes 50# Case	12" Round Steel Spikes 50# Case	10" Spiral Nylon Spikes 150-Count	10" Round Nylon Spikes 150-Count
						
Item 1900	SPIKE8BS	SPIKE10BS	SPIKE10BR	SPIKE12BR	SPIKE10NS	SPIKE10NR



Dimex Limited Lifetime Warranty

NovaEdge™ Paver Restraint products are guaranteed to be free from manufacturing defects and will not crack, rot, or deteriorate when handled and installed according to recommended guidelines.



28305 State Route 7
Marietta, OH 45750
www.edgepro.com

Phone: 740-374-3100
Toll Free: 800-334-3776
Fax: 740-374-5420